

MODULAR SEALS

MODEL LVLSMS



DESCRIPTION:

Modular Seals provide a method for permanently and hydrostatically sealing cylindrical objects of any size passing thru walls, floors, and ceilings. Designed for use as a permanent seal.

- Rated at 40 ft. of head pressure
- Engineered to resist aging and the effects of ozone, water, sunlight, and treatment plant chemicals
- NSF 61 and Factory Mutual Fire Approved materials available

MODEL NO.
LV-1200
LV-1275
LV-1300
LV-1315
LV-1325
LV-1340
LV-1360
LV-1400
LV-1410
LV-1425
LV1-475
LV-1500
LV-1525
LV-1575
LV-1615
LV-1650

16 INDUSTRY-LEADING SIZES

Nitrile seal elements, for oil, fuels, motor oil and kerosene, or for low durometer EPDM compound or silicone.

MODEL "C"

For use in water and waste water, EPDM Rubber. Bolts and nuts are carbon steel, zinc dichromated with a proprietary corrosion inhibiting coating.

MODEL "S-316"

For chemical processing and waste water treatment, EPDM Rubber. Bolts and nuts are 316 Stainless Steel.

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	